

**COMPACT FLUORESCENT HAND LAMP
CHL SERIES
EXPLOSION PROOF**

BELGIUM



A QUALITY PRODUCT

TECHNICAL DATA

- Type of Protection : Ex d IIA T6/T5 (for Zone 1 & 2)
- Conforming to : Standards IEC 60079-0/1
- Marking : Ex II2G Ex d IIA T6
- Degree of Protection : IP 66 acc.to IEC 60529
- Ambient Temp. (Ta) : -20° C to + 40° C or + 55° C
- Rated Voltage : 220 - 240 V.AC. 50/60Hz.
- Protection class for UL.: Class I, Division1 or 2 Group.C,D
: Class II, Division1 or 2 Groups.E,F,G
- Protection class for IEC: Zone1 and Zone 2



SPECIFICATION

- Lamp : Compact fluorescent
: PLS 11W. Warm white (900 lm.)
- Housing material : Copper-free aluminium with epoxy-polyester powder coated.
- Tube : Borosilicate glass
- Guard, screws : Stainless steel
- Ground clamp : Bronze, completed with 5 m. length of cable
- Connection : Sealing ring provided for external connection of
: cable O.D. 9-14 mm., or 15-19 mm.
- Sealing ring : Neoprene (CR) -25° C to + 100° C

CATALOGUE NUMBER AND DIMENSION

Lamp Watts	Cat.,No.	Volt
	Compact Fluorescent	
11	CHL11	220

