



BELGIUM

A QUALITY PRODUCT

PUSH BUTTON WITH PILOT LIGHT AND EMERGENCY

EPSLM SERIES

EXPLOSION PROOF



TECHNICAL DATA

Type of Protection	: Ex d IIB T6
Conforming to	: Standards IEC 60079-1 or UL 60079-0/1
Marking for test	: Ex II2G
Degree of Protection	: IP66 acc.To IEC 60529
Ambient Temp. (Ta)	: -20 ^o C to+ 55 ^o C Temp.class T6
Protection class for UL.	: Class I, Division 1, 2 Group.C,D
	: Class II, Division 1 or 2 Groups.E,F,G
Protection class for IEC	: Zone 1, 2
Conduit hub :	: 3/4" NPT.
Contact rating	: 3A. 110V.AC - 380V.AC , 12 , 24 V.DC.

SPECIFICATION

Body, cover and handle	: Copper-free aluminium
Bolts and operating shaft	: Stainless steel

OPTIONS

- Specify operating voltage code for lamp's transformer to Cat.,No.
1 - 110V.AC., 2 - 220V.AC., 3 - 380V.AC.
4 - 12V.DC., 5 - 24V.DC.
- ✦ Specify lens colour code to Cat.,No.
R - Red., G - Green, O - Orange,
B - Blue, W - White

CATALOGUE NUMBER

Number of contact	Symbol	Nameplate Marking	Cat.,No.
			Through-feed (2 hub)
Single Gang 1PL + 2 PB(1NO,1NC) + 1 (1NO,1NC) Push - Lock , Turn - Reset		RUN ,START,STOP and EMERGENCY STOP	EPSLM1 - 1111 <input type="checkbox"/> ✦

DIMENSION IN MM.

