

BELGIUM



A QUALITY PRODUCT

## EXIT LIGHT BATTERY PACK FOR FLUORESCENT AND COMPACT FLUORESCENT EXPLOSION PROOF EXIT SERIES



### TECHNICAL DATA

Type of Protection	: Ex de IIB T6
Conforming to	: Standards IEC 60079 - 0 to 1 or UL 60079-1
Marking for test	: Ex II2G
Degree of Protection	: IP 66 acc.To IEC 60529
Storage Temp. (Ta)	: -30° C to+ 65° C
Input voltage	: 220 VAC.+/- 10%, 50Hz.
Lamp Use/Back up	: 1 x 18w.,1 x 11w. / 2Hrs.,
Battery	: 6V,4AH. Standard charge 14-16 Hour
Mode Operating	: Maintained
Charging Period	: Constant Current 24 Hrs.
Construction	: Iron Sheet

### SPECIFICATION

Body material	: Marine Grade Copper-free aluminium alloy with polyester powder coated RAL7032 (GREY)
Lens	: Heat and impact resistant clear glass
Sing face	: White, Green acrylic with red,white colour letters. or aluminium
Standard hub size	: 3/4" NPT
Reflector	: Anodized aluminium

### CATALOGUE NUMBER AND DIMENSION

Lamp Watts	Temp. Class (Surface Temp.)		Cat.,No.
	40° C Ta	55° C Ta	
Fluorescent 1 x 18 W.	T6	T6	EXIT118
Compact 1 x 11W.	T6	T6	EXIT111

Type EXIT 118  
Type EXIT 111

