



BELGIUM

A QUALITY PRODUCT

SELECTOR SWITCHES ESL SERIES

EXPLOSION PROOF

TECHNICAL DATA

Type of Protection : Ex d IIB T6
 Conforming to : Standards IEC 60079-1 or UL 60079-0/1
 Marking for test : Ex II2G
 Degree of Protection 9 : IP65/66 acc.To IEC 6052
 Ambient Temp. (Ta) : -20° C to+ 55° C
 Protection class for UL. : Class I, Division1 or 2 Group.C,D
 : Class II, Division 1 or 2 Groups.E,F,G
 Protection class for IEC : Zone1and Zone 2



SPECIFICATION

Body, cover and handle : Copper-free aluminium
 Bolts and operating shaft : Stainless steel

OPTIONS

- For 2-positions with spring return, add suffix - *P* to Cat.,No.
- Silicone rubber on cover pushbutton
- Type *S* for IP66

CATALOGUE NUMBER

Number of contact	Diagram			Nameplate Marking	Cat.,No.	
	Left	Center	Right		Dead-end (1 hub)	Through-feed (2 hub)
2 - Positions						
1NO		-		OFF - ON	ESL 210 <input type="checkbox"/>	ESL 210H <input type="checkbox"/>
2NO		-		OFF - ON	ESL 220 <input type="checkbox"/>	ESL 220H <input type="checkbox"/>
1NO - 1NC		-		MAN. - AUTO	ESL 211 <input type="checkbox"/>	ESL 211H <input type="checkbox"/>
3 - Positions						
2NO				MAN.-OFF-AUTO.	ESL 320 <input type="checkbox"/>	ESL 320H <input type="checkbox"/>
2NC				<i>Specify</i>	ESL 302 <input type="checkbox"/>	ESL 302H <input type="checkbox"/>

DIMENSIONS IN MM.

